



RECOMMENDED PCB LAYOUT

FEATURES

Available in 10-68 circuits

MATERIAL

Contact material: Brass

Insulator Material: Thermoplastic, UL 94 V-0

FINISH

Contact Plated: Gold over Nickel

SPECIFICATIONS

Current Rating: 1A

Insulation resistance: 5000 M Ω min

Contact resistance: 20 m Ω max

Dielectric withstanding voltage: 500 VAC/DC

Operating Temperature: -45°C to 105°C

Part No. System

MM2532X - XX - X

□: Straight type
R: Right angle type

No. of circuits

□: Normal Part
G: ROHS Part
V: Lead Free

Base No.

LONG CHU ELECTRONICS CO. LTD

LCU

龍竹企業股份有限公司

			MATERIAL	UNIT	DESCRIPTION:		
			SEE LIST	mm	2.00mm Low Profile Header (Box Header)		
			DR.	RE.	GENERAL TOLERANCE		SIZE
A	NEW RELEASE	06/30/06	NORETA-		0. =±.50	0.° =±5°	A4
REV.	REV. RECORD	DATE	CHK.	APP.	0.0 =±.30	0.0° =±1°	SCALE
					0.00 =±.20		3.2/1
							P/N
							MM2532-R series
							REV.
							A
							SHEET NO.
							40023A