



RECOMMENDED PCB LAYOUT

Features:

- * Available in 10-64 circuits
- * Current Rating:3Amps
- * Insulator resistance:5000 M ohm min
- * Contact resistance:20m ohm max
- * Dielectric withstanding voltage:500VAC
- * Operating Temperature:-40°C to 105°C
- * Fully shrouded
- * Insulator material:Thermoplastic glass fiber(UL94 V-0)
- * Contact Plated:Gold over nickel
- * Mates with LCU M2540

PACKING

- * Packing:260 pcs / tray
- * Weight:1.4 g / pcs

Part No. System

M2532X - XX - X

Type No.

No.of circuits

□:Normal Part

G:ROHS Part

V:Lead Free

Base No.

LONG CHU ELECTRONICS CO. LTD

LCU

龍竹企業股份有限公司

			MATERIAL	UNIT	DESCRIPTION:		
			SEE LIST	mm	2.54mm Low Profile Header(Box Header)		
			DR.	RE.	GENERAL TOLERANCE	SIZE	P/N
A	NEW RELEASE	9/17/04"	IVY LIN		0. =±.50 0.° =±5°	A4	M2532-2*5-1
REV.	REV. RECORD	DATE	CHK.	APP.	0.0 =±.30 0.0° =±1°	SCALE	REV. SHEET NO.
					0.00 =±.20	---	A