



***FEATURES**

MATES WITH LCU P601 P601-R & H604
ACCEPTS LCU T304 SERIES, T304-H SERIES

***MATERIAL:**

INSULATOR MATERIAL: UL94V-2, NYLON 66 OR UL94V-0

***SPECIFICATION:**

CURRENT RATING: 7A
INSULATION RESISTANCE: 1000M Ω MIN.
DIELECTRIC WITHSTANDING VOLTAGE: 250VAC/DC
OPERATING TEMPERATURE: -40°C TO 105°C

HOW TO ORDER

H601X-X
 UL94V-2 (NATURAL)
 V0:UL94V-0 (WHITE)
 NORMAL PART
 G:R0HS PART
 V:For Lead Free Process
 BASE NO.

LONG CHU ELECTRONICS CO. LTD
LCU 龍竹企業股份有限公司

MATERIAL
SEE LIST

UNIT
mm

DESCRIPTION:
5.08mm 4p Power Supplier Socket Housing

SIZE
A4

TITLE:
H601 SERIES

SHEET NO.

DR.	KELLY	CHK.	APP.
REV.	REV. RECORD	DR.	DATE

ADD FEATURES and PART NO. SYSTEM	IVY LIN	10/01/02*
NEW RELEASE	NINA CHEN	01/12/01*

REV.	REV. RECORD	DR.	DATE
------	-------------	-----	------

REV.	REV. RECORD	DR.	DATE
------	-------------	-----	------

ADD FEATURES and PART NO. SYSTEM	IVY LIN	10/01/02*
NEW RELEASE	NINA CHEN	01/12/01*

REV.	REV. RECORD	DR.	DATE
------	-------------	-----	------

GENERAL TOLERANCE	0. ±±.50	0.° ±±5°
SCALE	0.0 ±±.30	0.0° ±±1°
SCALE	0.00 ±±.20	

REV.	REV. RECORD	DR.	DATE
------	-------------	-----	------

REV.	REV. RECORD	DR.	DATE
------	-------------	-----	------