



FEATURES

H200

- *Available in 2-16 circuits
- *UL 94V-0 Nylon 66
- *Mates with P200 series
- *Accepts with LCU T200 contact terminal
- *250V AC/DC 2A

T200

- *Spring phosphor bronze with Gold flash
- *Mates with LCU H200 series
- *Wire ranges 24-30 AWG
- *Insulation O.D 1.5mm Max.

Ordering and Dimensional Information—(mm)

Part No.	Dim.A
H200-02	5.80
H020-03	7.80
H200-04	9.80
H200-05	11.80
H200-06	13.80
H200-07	15.80
H200-08	17.80

Part No.	Dim.A
H200-09	19.80
H200-10	21.80
H200-11	23.80
H200-12	25.80
H200-13	27.80
H200-14	29.80
H200-15	31.80
H200-16	33.80

HOW TO ORDER

H200X-XX

Number of circuit
(available in 02~16 circuits)

□:NORMAL PART

G:ROHS PART

V:For Lead Free Process

BASE NO.

LONG CHU ELECTRONICS CO. LTD
龍竹企業股份有限公司

DESCRIPTION:

2.00mm Crimp Housing

REV.	NEW RELEASE	REV. RECORD	DATE	MATERIAL	SEE NOTE	UNIT	mm	GENERAL TOLERANCE	SIZE	P/N	SHEET NO.
A	NEW RELEASE		10/22/03*	DR. KELLY	RE.	mm		0. ±.50 0.0 ±.30 0.00 ±.20	A4 SCALE 1/4	H200 series	
REV.				CHK.	APP.					REV. A	