



FETATURES

Available in 02-24 circuits
 Mates with LCU H2052-M series
 Accepts with LCU T2052 series contact terminal

MATERIAL

Thermoplastic, UL94 V-2 or 94 V-0

SPECIFICATIONS

Current Rating: 9A
 Insulation resistance: 1000MΩ min
 Dielectric withstanding voltage: 1500VAC/DC for 60 sec.
 Operating Temperature: -45°C to 105°C

HOW TO ORDER

H2052X-XX



CIRCUITS	Dim. A	Dim. B	CIRCUITS	Dim. A	Dim. B
2		5.4	14	25.2	30.6
4	4.2	9.6	16	29.4	34.8
6	8.4	13.8	18	33.6	39.0
8	12.6	18.0	20	37.8	43.2
10	16.8	22.2	22	42.0	47.4
12	21.0	26.4	24	46.2	51.6

REV.	NEW RELEASE	REV. RECORD	DATE	MATERIAL	UNIT	DESCRIPTION:	SIZE	P/N	SHEET NO.
A	NEW RELEASE	REV. RECORD	11/30/06*	SEE NOTE	mm	4.20mm Mini Fit Housing	A4	H2052-2P series	
				DR. KELLY	RE.				
				CHK.	APP.				

LONG CHU ELECTRONICS CO. LTD
LCU
 龍竹企業股份有限公司

GENERAL TOLERANCE	0. ±±.50	0.° ±±5°	SCALE	1/1
	0.0 ±±.30	0.0° ±±1°	REV.	A