



SPECIFICATIONS:

Contact Resistance : 30mΩ max

Insulation Resistance : 100MΩ min. at DC 500V

Dielectric Withstand Voltage : AC 500V for one minute

(3)	HOUSING	THERMOPLASTIC	1	
(2)	PIN	0.6T Brass	1	SILVER PLATED
(1)	TERMINAL	0.4T Brass	1	NICKEL PLATED
NO.	DESCRIPTION	MATERIAL	Q'TY	FINISH

HOW TO ORDER

RCX-0561-A-X

HOUSING COLOR

Y:YELLOW
W:WHITE
R:RED
O:ORANGE
G:GREEN
BL:BLUE
(ANY COLOR CAN BE MADE)

SERIES NO.

TYPE NO.

□:Normal Part

G:ROHS Part

V:For Lead free Process

Base No.

RECOMMENDED PCB LAYOUT

REV.	REV. RECORD	DATE	MATERIAL	UNIT	DESCRIPTION:	SIZE	P/N
A	NEW RELEASE (F00137)	11/20/06"	SEE NOTE	mm	RCX JACK	A4	RC-0561-A SERIES
DR.	KELLY	RE.	DR. KELY	RE.	CHK.	SCALE	REV.
CHK.		APP.				1/2	A
							SHEET NO.

LONG CHU ELECTRONICS CO. LTD
LCU 龍竹企業股份有限公司