



RECOMMENDED PCB LAYOUT

NO.	DESCRIPTION	QTY	MATERIAL	REMARK
(1)	HOUSING(BLACK)	1	THERMOPLASTIC	UL-94HB
(2)	GROUND CONTACT	1	Phosphor Bronze t=0.3	NI:40-60 μ" THK.
(3)	TERMINAL	1	Phosphor Bronze t=0.4	TIN PLATED 100-150 μ" THK., NI:40-60 μ" THK.
(4)	TERMINAL	1	Phosphor Bronze t=0.4	TIN PLATED 100-150 μ" THK., NI:40-60 μ" THK.
(5)	TERMINAL	1	Phosphor Bronze t=0.4	TIN PLATED 100-150 μ" THK., NI:40-60 μ" THK.
(6)	TERMINAL	1	Phosphor Bronze t=0.4	TIN PLATED 100-150 μ" THK., NI:40-60 μ" THK.
(7)	WASHER(YELLOW)	1	THERMOPLASTIC	UL-94HB
(8)	OUTER CONTACT	1	Phosphor Bronze t=0.4	TIN PLATED 100-150 μ" THK., NI:40-60 μ" THK.
(9)	TERMINAL	1	Phosphor Bronze t=0.4	TIN PLATED 100-150 μ" THK., NI:40-60 μ" THK.
(10)	TERMINAL	1	Phosphor Bronze t=0.4	TIN PLATED 100-150 μ" THK., NI:40-60 μ" THK.

HOW TO ORDER

AJX-040-XX

□:Normal Part
G:ROHS Part
V:For Lead free Process

Series No.

Type No.

Base No.

LONG CHU ELECTRONICS CO. LTD
龍竹企業股份有限公司

MATERIAL		UNIT	
SEE NOTE		mm	
C	SIZE C CHANGE	05/03/05"	
B	ADD SIZE B	02/01/05"	
A	NEW RELEASE (F00137)	10/07/04"	
REV.	REV. RECORD	DATE	
PIN JACK+S JACK			
GENERAL TOLERANCE			
0. ±.50	0. ° ±5°	SIZE	P/N
0.0 ±.30	0.0 ° ±1°	A4	AJ-040-17B SERIES
0.00 ±.20		SCALE	REV. C SHEET NO.
		1/2	

